

| Díámetro | Anchura | ETRTO    | Modelo      | Dureza | Presión (PSI) | Presión (BAR) | Peso (gr) | Ancho Interior Llanta | Incluye pins de: |
|----------|---------|----------|-------------|--------|---------------|---------------|-----------|-----------------------|------------------|
| 16"      | 1,25    | (32-305) | Mini Velo   | R      | 90            | 6             | 280       | 17~20mm               | 21,5~23,5mm      |
| 16"      | 1,5     | (40-305) | Shield      | R      | 80            | 5.5           | 440       | 19~21mm               | 22,5~24,5mm      |
| 16"      | 1,25    | (32-349) | Mini Velo   | R      | 85            | 6             | 310       | 17~20mm               | 21,5~23,5mm      |
| 18"      | 1,25    | (32-355) | Mini Velo   | R      | 85            | 6             | 310       | 17~20mm               | 21,5~23,5mm      |
| 18"      | 1,5     | (40-355) | Shield      | R      | 80            | 5.5           | 440       | 19~21mm               | 22,5~24,5mm      |
| 20"      | 1,25    | (32-406) | Mini Velo   | R      | 85            | 6             | 360       | 17~20mm               | 21,5~23,5mm      |
| 20"      | 1,5     | (40-406) | Shield      | R      | 80            | 5.5           | 570       | 19~21mm               | 22,5~24,5mm      |
| 20"      | 1 1/8   | (28-451) | Semi Slick  | R      | 95            | 6.5           | 380       | 13~16mm               | 16,5~19,5mm      |
| 22"      | 1,5     | (40-501) | Shield      | R      | 80            | 5.5           | 550       | 19~21mm               | 22,5~24,5mm      |
| 24"      | 1 3/8   | (35-540) | WheelChair  | R      | 60            | 4,1           | 480       | 17~20mm               | 21,5~23,5mm      |
| 24"      | 1,5     | (40-540) | Shield      | R      | 80            | 5.5           | 590       | 19~21mm               | 22,5~24,5mm      |
| 24"      | 1,75    | (44-507) | Shield      | R      | 80            | 5.5           | 670       | 17~20mm               | 21,5~23,5mm      |
| 26"      | 1,75    | (44-559) | Razor Blade | H / R  | 65            | 4.6           | 800       | 17~20mm               | 21,5~23,5mm      |
| 26"      | 1 3/8   | (35-590) | Shield      | R      | 65            | 4.4           | 620       | 18~20mm               | 21,5~23,5mm      |
| 700      | 23C     | (23-622) | Slick       | H / R  | 120/105       | 8.5~7.5       | 370       | 13~15mm               | 16,5~18,5mm      |
| 700      | 25C     | (25-622) | New Slick   | H / R  | 115/105       | 7.8~7.2       | 434       | 16~18mm               | 19,5~21,5mm      |
| 700      | 28C     | (28-622) | Semi Slick  | H / R  | 105/95        | 7.2~6.5       | 460       | 14~16mm               | 17,5~19,5mm      |
| 700      | 32C     | (32-622) | Shield      | R      | 65            | 4.4           | 650       | 18~20mm               | 21,5~23,5mm      |
| 700      | 40C     | (40-622) | Shield      | R      | 65            | 4.4           | 730       | 19~21mm               | 22,5~24,5mm      |
| 700      | 28      | (28-622) | Portal      | H      | 110           | 7.6           | 495       | 17~20mm               | 21,5~23,5mm      |

R = Regular H = Hard