

Díámetro	Anchura	ETRTO	Modelo	Dureza	Presión (PSI)	Presión (BAR)	Peso (gr)	Ancho Interior Llanta	Incluye pins de:
16"	1,25	(32-305)	Mini Velo	R	90	6	280	17~20mm	21,5~23,5mm
16"	1,5	(40-305)	Shield	R	80	5.5	440	19~21mm	22,5~24,5mm
16"	1,25	(32-349)	Mini Velo	R	85	6	310	17~20mm	21,5~23,5mm
18"	1,25	(32-355)	Mini Velo	R	85	6	310	17~20mm	21,5~23,5mm
18"	1,5	(40-355)	Shield	R	80	5.5	440	19~21mm	22,5~24,5mm
20"	1,25	(32-406)	Mini Velo	R	85	6	360	17~20mm	21,5~23,5mm
20"	1,5	(40-406)	Shield	R	80	5.5	570	19~21mm	22,5~24,5mm
20"	1 1/8	(28-451)	Semi Slick	R	95	6.5	380	13~16mm	16,5~19,5mm
22"	1,5	(40-501)	Shield	R	80	5.5	550	19~21mm	22,5~24,5mm
24"	1 3/8	(35-540)	WheelChair	R	60	4,1	480	17~20mm	21,5~23,5mm
24"	1,5	(40-540)	Shield	R	80	5.5	590	19~21mm	22,5~24,5mm
24"	1,75	(44-507)	Shield	R	80	5.5	670	17~20mm	21,5~23,5mm
26"	1,75	(44-559)	Razor Blade	H / R	65	4.6	800	17~20mm	21,5~23,5mm
26"	1 3/8	(35-590)	Shield	R	65	4.4	620	18~20mm	21,5~23,5mm
700	23C	(23-622)	Slick	H / R	120/105	8.5~7.5	370	13~15mm	16,5~18,5mm
700	25C	(25-622)	New Slick	H / R	115/105	7.8~7.2	434	16~18mm	19,5~21,5mm
700	28C	(28-622)	Semi Slick	H / R	105/95	7.2~6.5	460	14~16mm	17,5~19,5mm
700	32C	(32-622)	Shield	R	65	4.4	650	18~20mm	21,5~23,5mm
700	40C	(40-622)	Shield	R	65	4.4	730	19~21mm	22,5~24,5mm
700	28	(28-622)	Portal	H	110	7.6	495	17~20mm	21,5~23,5mm

R = Regular H = Hard