



BEFORE YOU BEGIN: Prepare your tubeless set-up by installing the rim-tape and valve according to the manufacturer's guidelines.

1. Install the first bead of the tire around the rim.




2. Be sure to align the tubeless notch with the valve.



3. Install Tannus Armour under the tire and inside the bead of the rim.



4. Push second bead of the tire inside the bead of the rim.



5. Complete your tubeless setup by adding 2-4oz of sealant.



6. Inflate tire using a pump or air compressor and check for leaks.



INSTALLATION TIPS

TANNUS ARMOUR TUBELESS INSERTS ARE FOR TUBELESS TIRES AND RIMS ONLY.

Ensure you are familiar with setting up tubeless tires before proceeding with installation.

SEALANT: To save time you can pour sealant in the tire before pushing the second bead of the tire over the rim in step 4. If you do please skip step 5.

TOOLS: If you're struggling to get the second bead over the rim use tire levers or ask a friend for a hand.

VALVE CORE: Be sure to remove the valve core before filling with sealant and replace once the sealant is applied.

INFLATION: When inflating the tire a simple bicycle air pump is all that is needed. However, if you're having a difficult time getting the bead to set try using an air compressor.

WARNING

- THIS PRODUCT IS FOR TUBELESS BICYCLE TIRES ONLY.
- WE ARE NOT RESPONSIBLE FOR DAMAGE CAUSED DURING INSTALLATION UNLESS IT'S A MANUFACTURING DEFAULT.
- WE ARE NOT RESPONSIBLE FOR MISUSE OR TAMPERING OF THE TANNUS ARMOUR TUBELESS.

TANNUS WILL NOT BE LIABLE IF THESE GUIDELINES ARE NOT FOLLOWED THROUGH APPROPRIATELY.

1. Tannus Armour Tubeless Protects against flat tires, however, if the tubeless system itself (Tubeless Tape, Rim, sealant, or valve) is faulty, we are not responsible.
2. If a puncture occurs whilst Tannus Armour Tubeless is installed you can continue to ride for a limited period of time at a maximum of 10km/h.
3. It is important to understand how the Tannus Armour Tubeless is installed correctly. Please be sure to read the installation manual attached or visit Tannus.com for more information.
4. It is important to select the correct size Armour Tubeless. Please refer to the Tannus Armour Tubeless size guide.
5. Please be aware that selecting the incorrect size may cause damage when installing.
6. The Tannus Armour Tubeless can be reused upon multiple punctures, however, please check for damage to the Armour Tubeless prior to reinstalling.
7. We recommend to periodically check the condition of the tire, Armour, and tubeless system for wear and tear.
8. We advise you to install Tannus Armour using an approved Tannus dealer or technician. We are not responsible for any accidents or damages caused by malfunctions when installing with unapproved persons.
9. We encourage you to ride carefully at all times at a controlled speed especially when weather conditions are wet.
10. Tannus Armour protects your rim from damage, but we do not guarantee that rims will not break from impact.

MANUFACTURER'S WARRANTY/EXTRA INFO

You can return the unit to us and we will have the manufacturer repair or if need be replace the product for you providing the fault is found to be a result of either a manufacturing or material defect. If the manufacturer finds that the problem is due to misuse or neglect they reserve the right to levy a charge for the repair and return of the product.

All our products are manufactured to the relevant USA or European Safety Standards.

We will endeavour to take the greatest care to ensure that you receive your goods in perfect condition and that they are in good working order. However, if your goods are damaged or faulty, please contact customer care at tannustires.com/en/ on Complaints / Feedback / Recommendations.